



# PRODUCT SHEET

## MONVISO 8538 S3 SRC



### DESCRIPTION

Ankle shoes realized in high quality full grain leather with water-repellent properties and provided with protective toe cap and internal midsole in steel. The ankle collar and the tongue are soft padded; the outsole is provided with anti-slip anti-static, anti-torsion, anti-abrasion and shock absorbing properties/features.

### MATERIALS

<b>Upper</b>	Waterproof waxed full-grain leather	
<b>Lining</b>	Meryl® Actisystem: Ultra breathable and wear resistant lining	
<b>Sole</b>	Midsole in low density polyurethane Outsole in double-density thermo polyurethane	
<b>Protective toe cap</b>	<b>STEEL</b>	Impact resistance: until 200J Compression resistance: until 1500 kg
<b>Protective midsole</b>	<b>STEEL</b>	

<b>Product Code</b>	8538
<b>EN Standard</b>	EN ISO 20345:2011
<b>Safety Category</b>	S3 SRC
<b>Range of Sizes</b>	38 - 48
<b>Wide</b>	11
<b>Packaging</b>	6 pairs of same size

### SAFETY TECHNICAL SPECIFICATIONS

Description	Measurement Unit	EN ISO 20345:2011		Test Result	Description	Measurement Unit	EN ISO 20345:2011		Test Result
		Clause	Requirement				Clause	Requirement	
Impact resistance	mm	5.3.2.3	≥ 14	<b>15</b>	Upper: water penetration after 60 min	g	6.3	≤ 0,2	<b>0</b>
Compression resistance	mm	5.3.2.4	≥ 14	<b>16,5</b>	Upper: water absorption after 60 min	%	6.3	≤ 30	<b>4,2</b>
Penetration resistance	N	6.2.1.1	≥ 1100	<b>1320</b>	Lining: water vapour permeability	mg/(cm2*h)	5.5.3	≥ 2,0	<b>31,5</b>
Antistatic footwear: in wet condition	MΩ	6.2.2.2	≥ 0,1	<b>12</b>	Lining: water vapour coefficient	mg/cm2	5.5.3	≥ 20	<b>252</b>
Antistatic footwear: in dry condition	MΩ	6.2.2.2	≤ 1000	<b>210</b>	Outsole: abrasion resistance	mm3	5.8.3	≤ 150	<b>55</b>
Energy absorption of seat region (E)	J	6.2.4	≥ 20	<b>36</b>	Outsole: flexing resistance	mm	5.8.4	≤ 4	<b>0,5</b>
Water vapour permeability	mg/cm2*h	5.4.6	≥ 0,8	<b>2,1</b>	Outsole: interlayer bond strength	N/mm	5.8.6	≥ 4	<b>8,1</b>
Water vapour coefficient	mg/cm2	5.4.6	≥ 15	<b>19,1</b>	Outsole: hydrocarbons resistance	%	5.8.7	≤ 12	<b>2,5</b>

### SLIP RESISTANCE SPECIFICATIONS

Friction coefficient	Clause	Requirement	Test Result	Excess
Ceramic tile floor with NaLS ( 7°)	5.3.5.2	≥ 0,28	<b>0,39</b>	39%
Ceramic tile floor with NaLS	5.3.5.2	≥ 0,32	<b>0,37</b>	15%
Steel floor with glycerine (7°)	5.3.5.3	≥ 0,13	<b>0,14</b>	7%
Steel floor with glycerine	5.3.5.3	≥ 0,18	<b>0,19</b>	5%

### STORAGE, CARE AND MAINTENANCE

Panda Safety footwear should be stored in original packaging, storage temperature should not exceed 35°C, humidity should be less than 80% and without influence of direct sunlight. Footwear should be cleaned after each use; dry off the shoes not in proximity or in direct contact with stoves or other sources of heat. Carry out the periodic treatment of the uppers with adequate products containing wax, grease, silicone, etc. Avoid contact with aggressive chemicals and extreme temperatures. Verify the good state before each use.

The data indicated in this sheet are subject to modification without notice in case of evolution in materials.

All rights reserved. No part of this sheet can be reproduced in any form without written consent.

Italian Style at work