



EN ISO 20345:2022



HELEVO  
**XENO HIGH**  
66548-00L

**S3S FO SR**

**Size:** 35-48  
**Weight:** 550 gr.

**Fit:** 11

**Working Environment:**  
Multipurpose, Logistics and Light Industry, Components and Automotive, ESD Areas



**FEATURES**

**UPPER**  
No ladder, recycled Knit textile

**LINING**  
3D Green Air 320 gr.

**ANTISLIP LINING**  
DUALMICRO

**INSOLE**  
TALENT FIT D30

**TOE CAP**  
Nano Toe SXT

**RESISTANCE TO PERFORATION**  
KK7 Antiperforation recycled PS

**TYPE**  
Ankle boot

**SOLE**  
**PU DUAL-DENSITY CCYCLED® SR**  
Two-components PU sole, Outer and in-between sole with ESD compound. With recycled material Cycled®, highly non-slip SR Antislip standard.

**TECHNOLOGIES**

**Removable Insole**



Breathable anatomic insole. Durable recycled fabric with open cell foam. Absorbs shocks and decreases fatigue. Eliminates sweat with its high ability to evaporate it. Continuous comfort for months and months of use.



**Protection elements**



Composite toe cap, reinforced with carbon nanotubes. Resistant > 200J Non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable.



**Lateral stability**



Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



**Torsional stability**



Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



**Electrical features**



ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.

**Other**



Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.



**PU - PU**  
SOLE 66

**SLIP RESISTANCE**  
EN ISO 20345:2022

	FORWARD HEEL SLIP	BACKWARD FOREPART SLIP	FORWARD HEEL SLIP	BACKWARD FOREPART SLIP
<b>BASIC CERAMIC WITH NALS</b>	≥ 0.31	≥ 0.36	0,47	0,51
<b>SR CERAMIC WITH GLYCERINE</b>	≥ 0.19	≥ 0.22	0,36	0,35