



EN ISO 20345:2022



DIVENTURE
GARDENA
70538-05L

S3S FO *CI SC LG SR

Size: 36-48
Weight: 740 gr.

Fit: 11

Working Environment:
Building, Wood-metal carpentry,
Oil industry, Farming and
Gardening



FEATURES

UPPER

Greased Nubuk Leather Hydro
1,8-2,0 mm
Greased Nubuk Leather Hydro
1,8-2,0 mm

LINING

3D Green Air 320 gr.

ANTISLIP LINING

DUALMICRO

INSOLE

QRS02 Green

TOE CAP

Fiber cap SXT

RESISTANCE TO PERFORATION

KX Antiperforation recycled PS

TYPE

Ankle boot

SOLE

PU DUAL-DENSITY CCYCLED® SR

Two-component PU sole made from recycled Cycled® material with additional LG and SC requirements and SR characteristics.

TECHNOLOGIES

Removable Insole



Anatomical breathable insole. Resistant fabric with recycled open-cell foam that absorbs shocks and reduces fatigue. Eliminates sweat with its high ability to evaporate it. Continuous comfort for months and months of use



Protection elements



Composite toe cap with fiberglass. Resistant to over 200J. Recycled non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



Lateral stability



Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.

Torsional stability



Support made of rigid plastic material. It supports the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



Electrical features



ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.

Other



D30 materials are made using a combination of advanced polymer chemistry and cutting-edge science. It absorbs and dissipates energy during and impact, with superior stability, cushioning and anti-fatigue effect.



PU - PU
SOLE 70

SLIP RESISTANCE
EN ISO 20345:2022

	FORWARD HEEL SLIP	BACKWARD FOREPART SLIP	SLIP RESISTANCE
BASIC CERAMIC WITH NAILS	≥ 0.31	≥ 0.36	0,39
SR CERAMIC WITH GLYCERINE	≥ 0.19	≥ 0.22	0,31