



EN ISO 20345:2022



DIVENTURE
MARMOLADA
70539-05L

S7S FO *CI SC LG SR

Size: 36-48
Weight: 750 gr.

Fit: 11

Working Environment:
Building, Wood-metal carpentry,
Oil industry, Farming and
Gardening



FEATURES

UPPER
Greased Nubuk Dakar Leather
Hydro 1,8-2,0 mm
Reflex insert

LINING
3D Green Air 320 gr.

ANTISLIP LINING
DUALMICRO

INSOLE
QRS02 Green

TOE CAP
Fiber cap SXT

RESISTANCE TO PERFORATION
KX Antiperforation recycled PS

TYPE
Ankle boot

SOLE
PU DUAL-DENSITY CCYCLED® SR
Two-component PU sole made
from recycled Cycled® material
with additional LG and SC
requirements and SR
characteristics.

TECHNOLOGIES

Removable Insole
QRS02 GREEN

Anatomical breathable insole.
Resistant fabric with recycled open-
cell foam that absorbs shocks and
reduces fatigue. Eliminates sweat
with its high ability to evaporate it.
Continuous comfort for months and
months of use



Protection elements

KX GREEN RESISTANT TO 3.0 mm. NAILS
fibercap sxt

Composite toe cap with fiberglass.
Resistant to over 200J. Recycled non
metal perforation resistant insert to
over 1100 N with a 3.0 mm truncated
cone nail. Protection over the entire
sole of the foot. Flexible and
comfortable



Lateral stability

dynamic HC control
technology

Ergonomic rigid internal structure. It
houses the heel into the right seat,
adjusting the foot support and control
of the ankle sideways movements. It
keeps the foot tight to the shoe,
allowing the perfect fit.



Torsional stability

STABIL•ACTIVE

Support made of rigid plastic
material. It supports the heel bone,
the instep and tarsal joints, without
altering energy absorption. A support
for the natural movement of the foot;
it provides comfort and greater
stability.



Electrical features






ESD footwear discharge static
electricity and avoid damaging
surrounding objects; they are
designed in compliance with the
following standards: IEC EN
61340-5-1:2016 - IEC EN
61340-4-3:2018 - IEC EN
61340-4-5:2018.

Other

HDry
+WATERPROOF UPPER®

The HDry membrane is hydrophilic
with high perspiration capacity. It
guarantees high performance and
durability, facilitating the
maintenance of ideal conditions and
comfort for the user.



PU - PU		SLIP RESISTANCE	
SOLE 70		EN ISO 20345:2022	
BASIC CERAMIC WITH NAILS	FORWARD HEEL SLIP ≥ 0.31	0,39	
	BACKWARD FOREPART SLIP ≥ 0.36	0,42	
SR CERAMIC WITH GLYCERINE	FORWARD HEEL SLIP ≥ 0.19	0,20	
	BACKWARD FOREPART SLIP ≥ 0.22	0,31	